

Porter's Offset Wheel Harrow

12' to 25' Folding



Standard Features

- Comes with 28" x .315" Notched Disc Blades in Front & Smooth in Rear
- Dual Tapered Oil Bath Bearings
- Heavy Duty Fabricated Steel Spacers
- Furrow Filler Disc
- 1 5/8" Round Axle
- Bearing Wear Plates
- Adjustable Disc Blade Scrapers
- Heat Treated Alloy Steel Axles
- 4) 12.5 L x15 Highway Tires
- Depth Control Adjustments
- Transport Safety Locks
- Drawbar Jack Stand
- Self Leveling Hitch
- Two Tapered Roller Bearings on each 8 Bolt Hub
- Hub has Dust & Moisture Protection
- Hydraulic Cylinders and Hoses with Fittings and Quick Couplers that Reach the Rear of the Tractor
- Adjustable Gang Angles of 18, 20, & 20.5 degrees for Both Front & Rear Gangs



Porter's Offset Wheel Harrow

Model #	PWH12	PWH14	PWH16	PWH18	PWH19	PWH19F	PWH22F	PWH23F	PWH25F
Frame	Rigid	Rigid	Rigid	Rigid	Rigid	Folding	Folding	Folding	Folding
Cut Width	148"	168.5"	188"	209"	230"	230"	252.5"	272"	302"
Depth of Cut	9"	9"	9"	9"	9"	9"	9"	9"	9"
# of Disk	29	33	37	41	45	45	49	53	57
Trans Width	165"	191"	205"	230"	246"	162"	162"	162"	162"
DBPP*	5000-9200	5600-10700	6200-11900	7100-13200	8600-16000	8600-16000	9400-17500	10200-18300	11000-19100
DP HP	137-164	157-184	188-215	195-221	212-239	212-239	232-259	249-276	268-295
PTO HP	157-189	180-211	216-247	224-254	244-299	244-299	267-298	286-317	308-339
Lbs per disk	260	258	256	254	240	252	250	248	246
# of Bearing	8	12	12	12	12	16	16	16	16
Weight	7540	8514	10096	10414	10835	11250	12250	13144	14038



Call your local dealer for pricing and information:



Porter's Welding
 7061 County Road 24
 Orland CA 95963
 530.865.2221